

Directed graph algorithms

Data Structures and Algorithms for Computational Linguistics III
(ISCL-BA-07)

Cağrı Çöltekin
ccoltekin@ufa.uni-tuebingen.de

University of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2022/23

https://www.iscl.uni-tuebingen.de

Directed graphs

- Directed graphs are graphs with directed edges
- Some operations are more meaningful or challenging in directed graphs
- We will cover some of these operations, and some interesting sub-types of directed graphs
 - Transitive closure
 - Directed acyclic graphs
 - Topological ordering

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 1 / 1

Some terminology


- For any pair of nodes u and v in a directed graph
 - A directed graph is *strongly connected* if there is a directed path between u to v and v to u
 - A directed graph is *semi-connected* if there is a directed path between u to v or v to u
 - A directed graph is *weakly connected* if the undirected graph obtained by replacing all edges with undirected edges result in a connected graph

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 2 / 1

Checking strong connectivity

- Naive attempt: traverse the graph independently from each node (strongly connected if all traversals visit all nodes)
 - Time complexity: $O(n(n+m))$
- A better one:
 - traverse the graph from an arbitrary node
 - reverse all edges, traverse again
 - intuition: if there is a reverse path from D to A , then D is reachable from A
- Time complexity: $O(n+m)$
- Note: we do not need to copy the graph, we only need to do "reverse edge" queries



C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 3 / 1

Transitive closure

- We know that graph traversals answer reachability questions about two nodes efficiently
- Pre-computing all nodes reachable from every other node is beneficial in some applications
- The *transitive closure* of a graph is another graph where
 - The set of nodes are the same as the original graph
 - There is an edge between two nodes u and v if v is reachable from u
- For an undirected graph, transitive closure can be computed by computing the connected components

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 4 / 1

Computing transitive closure on directed graphs

- A straightforward algorithm:
 - run n graph traversals, from each node in the graph
 - add an edge between the start node to any node discovered by the traversal
 - time complexity is $O(n(n+m))$
- Floyd-Warshall algorithm is another well-known algorithm that runs more efficiently in some settings

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 5 / 1

Floyd-Warshall algorithm

for finding transitive closure


- Remember that transitive closure of a graph is another graph
- Floyd-Warshall algorithm is an iterative algorithm that computes the transitive closure in n iterations
- The algorithm starts with setting transitive closure to the original graph
- For $k = 1 \dots n$
 - Add a directed edge (v_i, v_j) to transitive closure if it already contains both (v_i, v_k) and (v_k, v_j)
- It is efficient if graph is implemented with an adjacency matrix and it is not sparse



C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 6 / 1

Floyd-Warshall demonstration



	A	B	C	D	E	F	G
A	F	T	F	T	T	T	T
B	T	F	F	T	T	T	T
C	T	T	F	T	T	T	T
D	T	T	F	F	T	T	T
E	T	T	F	T	F	T	T
F	T	T	F	T	T	F	T
G	T	T	F	T	T	T	F

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 7 / 1

Floyd-Warshall algorithm

adjacency matrix implementation

```
T = [row[] for row in G]
for k in range(n):
    for i in range(n):
        if i == k: continue
        for j in range(n):
            if j == i or j == k:
                continue
            T[i][j] = T[i][j] or \
                T[i][k] and T[k][j]
```


- Time complexity is $O(n^3)$
- Compare with repeated traversal: $O(n(n+m))$
 - Note that in a dense graph m is $O(n^2)$
- A version of this algorithm is also used for finding shortest paths in weighted graphs (later in the course)

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 8 / 1

Directed acyclic graphs

- Directed acyclic graphs* (DAGs) are directed graphs without cycles
- DAGs have many practical applications (mainly, dependency graphs)
 - Prerequisites between courses in a study program
 - Class inheritance in an object-oriented program
 - Scheduling constraints over tasks in a project
 - Dependency parser output (generally trees, but can also be more general DAGs)
 - A compact representation of a list of words:



C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 9 / 1


Directed acyclic graphs

Prereq	DEPARTMENT	COURSE	DESCRIPTION	PREREQS
	COMPUTER SCIENCE	COSC 452	INTERMEDIATE COMPILER DESIGN WITH A FOCUS ON DEPENDENCY RESOLUTION	COSC 452

https://www.stud.uni-tuebingen.de

DAG example

a (hypothetical) course prerequisite graph



C. Çöltekin, ISL / University of Tübingen

Winter Semester 2022/23 10 / 1

C. Çöltekin, ISL / University of Tübingen


Winter Semester 2022/23 11 / 1

Topological order

- A *topological ordering* of a directed graph is a sequence of nodes such that for every directed edge (u, v) u is listed before v
- A topological ordering lists 'prerequisites' of a node before listing the node itself
- There may be multiple topological orderings
- In the course prerequisite example, a topological ordering lists any acceptable order that the courses can be taken

Topological order example

course prerequisites – two alternative topological orders



Topological sort

algorithm

```

topo, ready = [], []
incount = {}
for u in nodes:
    incount[u] = u.indegree()
    if incount[u] == 0:
        ready.append(u)
while len(ready) > 0:
    u = ready.pop()
    topo.append(u)
    for v in u.neighbors():
        incount[v] -= 1
        if incount[v] == 0:
            ready.append(v)
    
```

- Keep record of number of incoming edges
- A node is ready to be placed in the sorted list if there no unprocessed incoming edges
- Running time is $O(n + m)$
- If the topological ordering does not contain all the edges, the graph includes a cycle

Topological sort

demonstration



Summary

- Some operations on directed graphs are more challenging.
- We covered
 - Finding strongly connected components
 - Finding the transitive closure of a digraph
 - DAGs and topological ordering
- Reading on graphs: [goodrich2013](#)
- Next:
 - More on graphs: shortest paths, minimum spanning trees

Acknowledgments, credits, references