

Shortest path algorithms

Data Structures and Algorithms for Computational Linguistics III
(ISCL-BA-07)

Çağrı Çöltekin
ccolt@informatik.uni-tuebingen.de

University of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2022/23

www.informatik.uni-tuebingen.de

Weighted graphs

- A *weighted graph* is a graph, where each edge is associated with a weight
- Weights can be any numeric value, but some algorithms require
 - Non-negative weights
 - "Euclidean" weights that are proper distance metrics
- Weights often indicate distance or cost, but they can also represent positive relations (e.g., affinity between nodes)
- Weight of a path is the sum of weights of the edges on the path



C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 1 / 19

Shortest path

Introduction/lecture Dijkstra SP on DAGs SP with negative weights

- Finding shortest paths on a weighted (directed) graph is one of the most common problems in many fields
- Applications include
 - Navigation
 - Routing in computer networks
 - Optimal construction of electronic circuits, VLSI chips
 - Robotics, transportation, finance, ...

C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 2 / 19

Shortest paths on unweighted graphs

BFS

Introduction/lecture Dijkstra SP on DAGs SP with negative weights

- A BFS search tree gives the shortest path from the source node to all other nodes
- The BFS is not enough on weighted graphs
- Shortest-cost path may be longer in terms of nodes visited



C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 3 / 19

Shortest paths on weighted graphs

variation of the problem

Introduction/lecture Dijkstra SP on DAGs SP with negative weights

- Different versions of the problem:
 - Single source shortest path: find shortest path from a source node to all others
 - Single target (sometimes called sink) shortest path: find shortest path from all nodes to a target node
 - Source to target: from a particular source node to a particular target node
 - All pairs: shortest paths between all pairs of nodes
- Restrictions on weights:
 - Euclidean weights
 - Non-negative weights
 - Arbitrary weights

C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 4 / 19

Dijkstra's algorithm

intro

Introduction/lecture Dijkstra SP on DAGs SP with negative weights

- Dijkstra's algorithm is a 'weighted' version of the BFS
- The algorithm finds shortest path from a single source node to all connected nodes
- Weights has to be non-negative
- It is a greedy algorithm that grows a 'cloud' of nodes for which we know the shortest paths from the source node
- The new nodes are included in the cloud in order of their shortest paths from the source node

C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 5 / 19

Dijkstra's algorithm

the algorithm

Introduction/lecture Dijkstra SP on DAGs SP with negative weights

```
1: D[s] ← 0
2: for each node v ≠ s do
3:   D[v] ← ∞
4: Q ← nodes
5: while Q is not empty do
6:   Remove node u with min D[u] from Q
7:   for each edge (u, v) do
8:     if D[u] + w(u, v) < D[v] then
9:       D[v] ← D[u] + w(u, v)
10: D contains the shortest distances from s
```

- We maintain a list D of minimum know distances to each node
- At each step
 - we take closest node out of Q
 - update the distances of all nodes
- Can be more efficient if Q is implemented using a (adaptable) priority queue


C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 6 / 19

Dijkstra's algorithm

demonstration

Introduction/lecture Dijkstra SP on DAGs SP with negative weights




C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 7 / 19

Dijkstra's algorithm

demonstration

Introduction/lecture Dijkstra SP on DAGs SP with negative weights




C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 8 / 19

Dijkstra's algorithm

demonstration

Introduction/lecture Dijkstra SP on DAGs SP with negative weights




C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 9 / 19

Dijkstra's algorithm

demonstration

Introduction/lecture Dijkstra SP on DAGs SP with negative weights




C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 10 / 19

Dijkstra's algorithm










demonstration

Introduction/lecture Dijkstra SP on DAGs SP with negative weights



C. Çöltekin, IM | University of Tübingen

Winter Semester 2022/23 11 / 19



Introduction/Introduction Dijkstra SP on DAGs SP with negative weights

Dijkstra's algorithm complexity

- In general, complexity is $O(|\text{In}_{\text{adj_min}}|n + |\text{In}_{\text{adj_max}}|m)$
- With list-based implementation of Q: $O(m + n^2) = O(n^2)$
- With a priority queue: $O((m + n) \log n)$

```

1: D[s] ← 0
2: for each node v ≠ s do
3:   D[v] ← ∞
4: Q ← nodes
5: while Q is not empty do
6:   Remove node u with min D[u] from Q
7:   for each edge (u, v) do
8:     if D[u] + w(u, v) < D[v] then
9:       D[v] ← D[u] + w(u, v)
10: D contains the shortest distances from s
  
```

C. G. Kokkoris, MSR | University of Salzburg Winter Semester 2022/23 8 / 18

Introduction/Introduction Dijkstra SP on DAGs SP with negative weights

Shortest-path tree

- The way we introduced, the Dijkstra's algorithm does not give the shortest-path tree
- Similar to traversal algorithms, we can extract it from distances D
- Running time is $O(n^2)$ (or $O(n + m)$)

```

1: T ← ∅
2: for u ∈ D - {s} do
3:   for each edge (v, u) do
4:     if D[u] == D[v] + w(v, u) then
5:       T ← T ∪ {v, u}
  
```

C. G. Kokkoris, MSR | University of Salzburg Winter Semester 2022/23 11 / 18

Introduction/Introduction Dijkstra SP on DAGs SP with negative weights


Shortest-paths on DAGs

- The shortest path can be found more efficiently, if the graph is a DAG
- The algorithm is similar to Dijkstra's, but simpler and faster
- Only difference is we follow a topological order
- The algorithm will also work with negative edge weights

C. G. Kokkoris, MSR | University of Salzburg Winter Semester 2022/23 11 / 18


Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration




Shortest-paths on DAGs

demonstration



Shortest-paths on DAGs

demonstration




Shortest-paths on directed graphs

with negative weights - without negative cycles

- Single-source shortest path problem can also be solved efficiently for any directed graph
 - including cycles (no DAG requirement)
 - including negative weights
 - excluding negative cycles
- The algorithm is known as Bellman-Ford algorithm
 - Similar to earlier algorithms, initialize $D[s] = 0, D[v] = \infty$
 - Make n passes over the edges
 - Update distances for each edge (relax edges)
 - Stop if there were no changes at the end of a pass


Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration




Bellman-Ford algorithm

demonstration



Bellman-Ford algorithm

demonstration




edges

1 → 2
1 → 4
2 → 4
2 → 5
3 → 2
3 → 4
5 → 3
5 → 4

Bellman-Ford algorithm

demonstration




edges

1 → 2
1 → 4
2 → 4
2 → 5
3 → 2
3 → 4
5 → 3
5 → 4

Bellman-Ford algorithm

demonstration




edges

1 → 2
1 → 4
2 → 4
2 → 5
3 → 2
3 → 4
5 → 3
5 → 4

Bellman-Ford algorithm

demonstration



edges

1 → 2
1 → 4
2 → 4
2 → 5
3 → 2
3 → 4
5 → 3
5 → 4

Summary

- Shortest path algorithms are one of the most applied graph algorithms
- We revised three algorithms
 - Dijkstra's: non-negative weights, general algorithm
 - For DAGs: unrestricted weights, following topological order
 - Bellman-Ford: no negative cycles, digraphs

• Reading: [goodrich2013](#)

Next:

- Minimum spanning trees
- Reading: [goodrich2013](#)

Acknowledgments, credits, references